

Dome cameras

DDZ3032SA **Panther**



New!

- HiRes UWDR PTZ colour dome camera
- HiRes zoom lens: 32x equivalent optical zoom
- 1/3" sensor DPS powered by **CamJinPIX®**
- Dynamic range up to 120 dB
- Progressive Scan
- 540 TV lines
- Slow shutter for night vision
- Sensitivity 0.8 lux (0.2 lux in Slow Shutter)
- Image stabilization (optional)
- Auto focus / manual focus override
- Serial remote control - multi protocol support
- Dimensions (DxH): 125x176mm

DDF3000A3(-DN)



New!

- HiRes UWDR colour minidome with **tri-axis adjustment**
- Variofocal lens F 1.2 DC-Iris/2.9-10mm (standard*)
- 1/3" sensor DPS powered by **CamJinPIX®**
- Dynamic range up to 120 dB
- Progressive Scan
- 540 TVL; 720x540 pixels
- Slow Shutter up to 8x
- Sensitivity 0.8 lux (0.2 lux in Slow Shutter) (-DN): 0.3 lux (0.06 lux in Slow Shutter)
- Dimensions (DxH): 140x95mm

DDF3000APV **Picodome**



New!

- HiRes UWDR colour picodome
- HiRes boardlens F 1.4/3.6mm
- 1/3" sensor DPS powered by **CamJinPIX®**
- **Vandalism-resistant** housing (IP 66)
- Ø 57 mm polycarbonate dome cover
- Dynamic range up to 120 dB
- Progressive Scan
- 540 TVL; 720x540 pixels
- Slow Shutter up to 8x
- Sensitivity 1.0 lux (0.2 lux in Slow Shutter)
- Dimensions (DxH): 57x60mm



Also available as in-ceiling version!



DDF3000A(-DN)



- HiRes UWDR colour minidome
- Variofocal lens F 1.2/2.9-10mm (standard*)
- 1/3" sensor DPS powered by **CamJinPIX®**
- Dynamic range up to 120 dB
- Progressive Scan
- 540 TVL; 720x540 pixels
- Slow Shutter up to 8x
- Sensitivity 0.8 lux (0.2 lux in Slow Shutter) (-DN): 0.3 lux (0.06 lux in Slow Shutter)
- Dimensions (DxH): 140x95mm

DDF3000AV(-DN)



- HiRes UWDR colour minidome
- Variofocal lens F 0.95 DC-Iris/2.8-8mm (standard*)
- 1/3" sensor DPS powered by **CamJinPIX®**
- **Vandalism resistant**: IP 67 housing
- Dynamic range up to 120 dB
- Progressive Scan
- 540 TVL; 720x540 pixels
- Slow Shutter up to 8x
- Sensitivity 0.5 lux (0.1 lux in Slow Shutter) (-DN): 0.2 lux (0.04 lux in Slow Shutter)
- Dimensions (DxH): 143x113mm

DDF3000IPV(-DN)



- HiRes UWDR colour IP dome camera
- Variofocal lens F 0.95 DN/2.8-8mm (standard*)
- 1/3" sensor DPS powered by **CamJinPIX®**
- **Vandalism resistant**: IP 67 housing
- Dynamic range up to 120 dB
- Progressive Scan
- 540 TV lines; 720 x 540 pixels
- Sensitivity 0.5 lux (0.1 lux in Slow Shutter) (-DN): 0.2 lux (0.04 lux in Slow Shutter)
- Transfer rate: up to 30fps@FullD1
- Format: MPEG-2/-4, MJPEG, H.263
- Integrated web server
- Dimensions (DxH): 140x113mm

* (Further) lenses available on request – for more information please visit our website. The use of day/night lenses is recommended for IR lighting.

Please note!

More information on our products can be found at:
www.dallmeier-electronic.com

Box cameras

DF3000A(S)(-DN)



- HiRes UWDR colour box camera*
- 1/3" sensor DPS powered by **CamLinPIX®**
- Dynamic range up to 120 dB
- Progressive Scan
- 540 TVL; 720x540 pixels
- Slow Shutter up to 8x
- Sensitivity at 0.95; 50 IRE
0.5 lux (0.1 lux in Slow Shutter)
(-DN): 0.2 lux (0.04 lux in Slow Shutter)
- Mechanical Day/Night switcher
- Dimensions DF3000A:
45x45x108mm (without lens)
- Dimensions DF3000AS:
45x45x73mm (without lens)

DF3000IP(-DN)



- HiRes UWDR colour IP box camera
- Variofocal lens F 0.95 DN/2.8-8mm (standard*)
- 1/3" sensor DPS powered by **CamLinPIX®**
- Dynamic range up to 120 dB
- Progressive Scan
- 540 TV lines; 720 x 540 pixels
- Sensitivity at 0.95; 50 IRE
0.5 lux (0.1 lux in Slow Shutter)
(-DN): 0.2 lux (0.04 lux in Slow Shutter)
- Mechanical Day/Night switcher
- Transfer rate: up to 30fps@FullD1
- Format: MPEG-2/-4, MJPEG, H.263
- Integrated web server
- Dimensions (WxHxL):
45x45x112mm (without lens)

Dome camera CCD

DDZ3018(26)A(-DN)



- HiRes PTZ colour dome camera
- Zoom lens: 18x/26x optical zoom, additionally 12x digital zoom
- 1/4" CCD-sensor
- 480 TV lines horizontal
- Sensitivity DDZ3018A 0.7 lux
(-DN): 0.01 lux in B/W
- Sensitivity DDZ3026A 1.0 lux
(-DN): 0.1 lux in B/W
- Panning speed: max. 390°/sec.
- 248 programmable preset positions
- 8 programmable tours and 4 patterns
- 8 dynamic privacy zones
- Dimensions (DxH): 125x176mm

Module cameras

New!

MDF3000A-B



- HiRes UWDR colour module camera
- Variofocal lens F1.2/2.9-10mm
- 1/3" sensor DPS powered by **CamLinPIX®**
- Dynamic range up to 120 dB
- Progressive Scan
- 540 TV lines; 720x540 pixels
- Slow Shutter up to 8x
- Sensitivity 0.8 lux
(0.2 lux in Slow Shutter)
- Dimensions:
41x41x33 mm (without lens)

MDF3000A-CS



- HiRes UWDR colour module camera
- Integrated CS-mount lens Fo.95/2.8-8mm
- 1/3" sensor DPS powered by **CamLinPIX®**
- Dynamic range up to 120 dB
- Progressive Scan
- 540 TV lines; 720x540 pixels
- Slow Shutter up to 8x
- Sensitivity 0.5 lux
(0.1 lux in Slow Shutter)
- Dimensions:
45x45x35 mm (without lens)

MDF3000A-M



- HiRes UWDR colour module camera
- Integrated micro lens F1.4/3.6mm
- 1/3" sensor DPS powered by **CamLinPIX®**
- Dynamic range up to 120 dB
- Progressive Scan
- 540 TV lines; 720x540 pixels
- Slow Shutter up to 8x
- Sensitivity 1.0 lux
(0.2 lux in Slow Shutter)
- Dimensions:
41x41x31 mm (without lens)

* (Further) lenses available on request – for more information please visit our website. The use of day/night lenses is recommended for IR lighting.

Please note!

More information on our products can be found at:
www.dallmeier-electronic.com